

Water Chiller



Technical data

Model		Ø1.6 x 3m	Ø1.6 x 6m	Ø1.6 x 9m	Ø1.6 x 12m
Capacity	bph	1000	2000	3000	4000
Diameter	mm	1600	1600	1600	1600
Length	mm	3000	6000	9000	12000
Width	mm	1820	1820	1820	1820
Height	mm	1830	1830	1830	1830
Weight	kh	900	1470	1550	2400
Air blower power	kW	3	3	3	3
Drive motor power	kW	0.75	0.75	0.75	0.75
Total installed power	kW	3.75	3.75	3.75	3.75
Est. volume	l	3000	6000	9000	12000
Est. water consumption	l/bird			2.5	



DUTCH POULTRY TECHNOLOGY B.V.

Hillegom, The Netherlands

www.dutch-poultry-tech.com

This information corresponds to the most recent available information at the time of publication. The construction, composition and execution of the product are subject to future modification, without notice. All given figures are indicative estimates. No rights can be derived from this publication.



Key Benefits

- Ideal for washing and pre-chilling eviscerated poultry prior to weighing, portioning and packing
- Prevents deterioration in meat quality and microbial growth by lowering the carcass temperature
- Flexible set-up: standard sections of 3 meters long and a diameters of 1600 or 2100 mm, which can be combined to match any production capacity
- Supplied with an air blower and control panel
- cold water aggregate or flake ice instalation no included but available on customer request
- Made of stainless steel and other non-corrosive materials



DUTCH POULTRY TECHNOLOGY B.V.

Hillegom, The Netherlands

www.dutch-poultry-tech.com

This information corresponds to the most recent available information at the time of publication. The construction, composition and execution of the product are subject to future modification, without notice. All given figures are indicative estimates. No rights can be derived from this publication.