



pluck & play solutions.

ARRIVAL | KILLING AND PLUCKING | **EVISCERATION** | CHILLING | WEIGHING | CUT-UP | FILLETING & DEBONING | PACKING

Automatic Final Inspection Machine



Key Benefits

- Driven by the overhead conveyor
- Quick removal of remaining impurities in the carcass by vacuum
- Machine is easy to maintain
- Reduced noise level due to special air valve
- Quick and easy cleaning
- Safety sensor which automatically halts the evisceration line upon detecting a machine jam or breakdown, preventing further damage to the line
- Made of stainless steel and other non-corrosive materials
- Supplied with receiving bin with central drain
- Height adjustment device

Technical details

Model		FC7	FC14	FC15	FC20
Capacity	bph	3000	6000	6500	10000
Live weight*	g	900 - 3200	900 - 3200	900 - 3200	900 - 3200
Number of units	n	7	14	15	20
Shackle pitch	inch	12	6	8	6
Length	mm	1600	1600	1600	1600
Width	mm	1300	1300	2100	2100
Height	mm	2000	2000	2600	2600
Weight	kg	600	600	800	800
Water connection	BSP	1/2"	1/2"	1/2"	1/2"
Water usage	m3/h	0.5	0.5	0.5	0.5

* max weight variance in one flock is +/- 150g in case of live weight 700 - 1200 grams and +/- 300g in case of live weight 1200 - 1700 grams